2. Specifications

***T*he descriptions and characteristics given in this booklet are given for information purposes only and are subject to modification without notice.**

TELEVISION PART	
Colour systems	PAL(option) / SECAM(option) (UK;PAL)
TV standards	L/L'(option), B/G(option), D/K(option) (UK;I)
Number of channels	100 programmes
Reception range/cable TV	Hyperband/interband tuner
Aerial input	75 Ohms, coaxial cable
VCR PART	
Format	VHS standard (PAL / SECAM(option) / MESECAM(option) / NTSC in playback only)
Heads	Video: 2 rotary heads, LP(option), 4 Heads(option) Audio/Control: 1 stationary head (linear) Erase: 1 full track erase head System Video Normal CCIR System Audio Mono / NICAM&A2-STEREO
Luminance	FM azimuth recording
Colour	Down converted subcarrier phase shifted direct recording
FF/REW time	Less than 100 seconds in FF with E-120
Wow and flutter (WTD)	0.4% maximum (SP)
Frequency response	100 Hz - 8 KHz
GENERAL	
Power supply	220-240V~, 50Hz (110-260V~, 50/60Hz; option),(160-300V~50/60Hz;Russia)
Consumption	14"15" (50W) 20"/21" (60W)
Audio output power	14"15" (2W) 20" (2W) 21" (1.0Watts x 2)
Number of loudspeakers	14"/15"/20" (1) 21" (2)
Tube size	14" (37cm/34cmV) 15" (39cm/36cmV) 20" (51cm/48cmV) 21" (55cm/51cmV)
Tube type	BLACK MATRIX
Sockets	1 full RGB SCART on the rear 1 RCA input (audio and video) on the front Earphones output (3.5 mm mini-jack) 1 aerial/cable TV coaxial input
Dimensions (W x D x H)	14" (368 x 390 x 381) 15" (411 x 401 x 417) 20" (486 x 473 x 485) 21" (520 x 495 x 508)
Weight	14" (11.1 kg) 15" (14.8 kg) 20" (19 kg) 21" (23.4 kg)
Operating temperature	5°C - 40°C (41°F - 104°F)
Relative humidity	10% - 75%

MEMO